



Light Duty Wall Mount Intercom

Model AD-28LD-MV

Designed for single-channel, two-way indoor communication applications. Features include integrated Gain control, Talk/Listen/Call switch, fabricated aluminum housing with rugged powder coat finish (Type 1X, IP10), reliable 25-watt speaker and balanced line output. These light duty units are UL, CSA Certified and are designed for multi-voltage operation: 24VDC, 120VAC and 240 VAC, 50/60Hz.

- Light duty industrial intercom for indoor applications
- Single channel, two-way communications
- Integrated Gain control and Talk/Listen/Call switch
- Balanced line output
- 25 watt speaker
- Fabricated aluminum housing with rugged powder coat finish
- Multi-voltage operation: 24VDC, 120VAC and 240VAC
- UL, CSA Certified
- Type 1X, IP10 enclosure
- Field configurable master/slave operating mode
- Remote power capable @24VDC
- Auxiliary signal activation contact



Model	Voltage Current	Operating Current	Stand-by Response	Frequency
AD-28LD-MV	24VDC	120mA	60mA	150Hz to 12KHz
	120VAC	80mA	60mA	150Hz to 12KHz
	240VAC	40mA	30mA	150Hz to 12KHz

Product Specifications

Speaker Rating	30 watt	30 watt
Operating temperature	-31°F to 150°F	-50°C to 66°C
Net weight	3.12 lbs	1.41 Kg
Shipping weight	3.56 lbs	1.62 Kg
Dimensions		
Height	8.00 in	20.32 cm
Width	6.88 in	17.48 cm
Depth	3.02 in	7.67 cm

